

BADUJET[®] Active Version 2

Compact overhang unit for beginners.
For small and above ground pools.

Field of application

For upgrading all pool models, as an attraction, for fitness training, as a wave or bubble bath, for underwater massages (consult physician), for endless, no-turn swimming even in the smallest pool.

Design

Water is drawn in through the suction inlet at the bottom of the unit using a powerful pump and led back into the pool through a strong jet via an adjustable nozzle.

For recommended accessories see page 32.

Materials used

Housing PE
Interior parts ABS/stainless steel
Control elements ABS
Suction/pressure line PVC/ABS
Hand rail stainless steel

Technical data at 50 Hz	BADUJET Active Version 2	21-40/54 H
Pump flow rate (m ³ /h)	1~	20
Voltage	1~	1~ 230 V
Power input P ₁ /output P ₂ ¹⁾ (kW)	1~	1.10/0.75
Number of nozzles (Ø 28 mm)		1
Flow pressure at nozzle (bar)	1~	0.80
Flow velocity in centre 2 m from the nozzle (m/s)	1~	0.80
Max. massage pressure (bar) max.	1~	1.20
Multi-directional swivel nozzle (degrees)		60
Net weight (kg)	1~	21.00

For more detailed information regarding the motor protection please see page 38.

Technical data may vary.

Article no	Description	Voltage	Power output P ₂
231.5100.000	BADUJET Active Version 2	1~ 230 V	0.75 kW
233.1500.000	Telescopic foot		

The pumps in the counter swim units can be used for pool water with a salt concentration of up to 0.5 %, i.e. 5 g/l.
For higher salt concentrations please contact us.



< Also available with
a telescopic foot for
above ground pools



Dimensions

Detailed dimensions available on request or at badu.de

