

BADU® Delta Eco VS

New high-class standard with speed control.
High-quality filter circulation pumps for professionals.

Field of application

Swimming pool water circulation through a filter system.
The pump can be installed max. 3 m above or below water level.

Design

Monoblock-type pump with integrated strainer tank.
The bellow-type mechanical seal is mounted on a plastic shaft protector sleeve. Motor/pump shaft has no contact with the pool water providing complete electrical separation.
Strainer tank capacity approx. 4 l
Strainer basket mesh size approx. 2.2 x 2.2 mm

Can be controlled with the BADU Eco Logic pump remote control.
See page 118.

Materials used

Pump casing PP GF 30
Intermediate housing PP GF 30
Gland housing PP GF 30
Unions/glue sockets ABS/PVC-U
Diffuser PP GF 30
Impeller PPE GF 30
Strainer basket PP
Lid PC, transparent/PA 66 GF 30
Mechanical seal carbon/ceramic/NBR
Screws stainless steel
Elastomers NBR/viton

Technical data at 50/60 Hz		BADU Delta Eco VS
Inlet Sa/outlet connection Da ⁴⁾		63/63
Rec. inlet/outlet pipe, PVC pipe, d ⁴⁾		63/63
Power input P ₁ /output P ₂ ¹⁾ (kW)	1 ~ 230 V	0.03-1.40/0.01-1.10
Rated current (A)	1 ~ 230 V	0.50-6.10
Net weight (kg)	1 ~	14.00

For more detailed information regarding the motor protection please see page 143.

Technical data may vary.

Article no	Description	Voltage	Power output P ₂
210.3281.138	BADU Delta Eco VS	1 ~ 230 V	1.10 kW


Universal opening device included in delivery. See page 132.



Transparent lid with integrated LED lighting



Impeller fan and guard for reduced operating noise



see key

Performance

Dimensions

Detailed dimensions available on request or at badu.de

