BADU® Eco Touch-Pro II



As a revolutionary innovation, with patented permanent magnet motor, the BADU Eco Touch-Pro II sets new standards in energy consumption, operating costs and water quality. The three variable motor speeds can be programmed individually. They can be set from 1000 to 2830 rpm in steps of 50. The values 2000, 2400 and 2830 rpm are pre-set. This BADU GREEN pump can be controlled using the BADU Eco Touch II and BADU Eco Logic control.

Details

Class: ALLROUND
Filter size in mm: 400 - 500
Flow rate Q in m³/h: max. 25
Installation: Built-in pool
Motor performance in kW (P2): max. 0,75
Pool equipment: Circulation pumps
Pool size in m³: 30 - 90, 30 - 90
Pool type: Naturpool / Schwimmteich
Strainer basket in mm: ca. 3,2 x 2,6
Strainer capacity in l: ca. 3, ca. 3
Total head H in m WS: max. 15

Materials used

Diffuser: PA 6 GF 15
Gland housing: PP TV 40, PP TV 40
Impeller: PA 66 GF 30
Intermediate housing: PP TV 40, PP TV 40
Mechanical seal: carbon / ceramic / NBR
Pump casing: PP TV 20, PP TV 20
Screws: Edelstahl, verzinkt
Strainer basket: PP

Miscellaneous

The pumps, as described, can be used for pool water with a salt concentration of up to 0.5%, i.e. 5

g/l.
For higher salt concentrations please contact the company SPECK Pumpen.

Downloads

- 3D model
- Spare parts list
- Catalogue page
- Characteristics
- EC declaration of conformity
- Dimensional drawing