

# BADU<sup>®</sup> 21-41/54H G



The BADU 21 range pumps are designed for the specific demands of bath tubs, whirlpools, counter swim units and cleaning devices. All models in this range are non-self-priming circulation pumps, which cannot handle air. These pumps are to be installed below the water level in order for the pool water to drain independently.

## Details

Flow rate Q in m<sup>3</sup>/h: 18

Motor performance in kW (P2): 0,75

Pool size in m<sup>3</sup>: 1 - 30

Total head H in m WS: 10

## Materials used

Impeller Lauf (Ausführung H): PPE GF 30 (PP GF 30), PPE GF 30 (PP GF 30)

Lid/Stand: PP TV 40, PP TV 40

Mechanical seal: carbon / ceramic / NBR

Pump casing: PP TV 40

Screws: Stahl, verzinkt / Edelstahl

## Field of application

Jet pump for jetted bath tubs, whirlpools, massage stations, air conditioning and cleaning units with a flow rate of up to 30 m<sup>3</sup>/h.

## Design

Monoblock-type pump with a closed bellow-type mechanical seal mounted on a plastic shaft protector sleeve. Motor/pump shaft has no contact with the pool water providing complete electrical separation. Discharge outlet swivels by 90°. The unit may be installed in a vertical

position with the pump facing downwards. Threaded inlet and outlet connections suitable for special union.

## Motors

Special motors on request. Additional motors with 3~ star-delta 400/230 V on request.

## Miscellaneous

Standard terminal box position on the top.

Attach vertically installed pumps to consoles on site with motor feet.

Self-draining for vertical installation.

The above mentioned pumps can be used for pool water with a salt concentration of up to 0.5%, i.e. 5 g/l.

For higher salt concentrations please contact the company SPECK Pumpen.

## Downloads

- [General operation manual](#)
- [Spare parts list](#)
- [Catalogue page](#)
- [Characteristics](#)
- [EC declaration of conformity](#)
- [Dimensional drawing](#)