

BADU[®] Delta 28



The BADU Delta swimming pool pump has a maintenance-free motor with high performance ball bearings and a stainless steel motor shaft. It is especially quiet and efficient due to newly configured hydraulics. LED lighting in the transparent lid aids sight inspections. Inset drain plugs avoid risk of breakage and highly efficient technology leads to higher flow rates with lower energy consumption.

Details

Class: PREMIUM
Connection: 230V, 400V
Flow rate Q in m³/h: 28
Installation: Built-in pool
Motor performance in kW (P2): 1,00
Pool equipment: Circulation pumps
Pool type: Innenpool
Strainer basket in mm: ca. 2,2 x 2,2
Strainer capacity in l: ca. 4
Total head H in m WS: 8

Materials used

Impeller: PPE GF 30
Intermediate housing: PP GF 30
Lid: PC, transparent / PA 66 GF 30
Mechanical seal: carbon / ceramic / NBR
Pump casing: PP GF 30
Screws: Edelstahl
Strainer basket: PP

Field of application

Swimming pool water circulation through a filter system. The pump can be installed max. 3 m above or below water level.

Design

Monoblock-type pump with integrated strainer tank. Motor/pump shaft has no contact with the pool water, providing complete electrical separation.

Motors

Special motors on request.

Miscellaneous

Also available in special design. The pumps, as described, can be used for pool water with a salt concentration of up to 0.5%, i.e. 5 g/l. For higher salt concentrations please contact the company SPECK Pumpen.

Downloads

- [3D model](#)
- [Spare parts list](#)
- [Catalogue page](#)
- [Characteristics](#)
- [EC declaration of conformity](#)
- [Dimensional drawing](#)