BADU® 43/15



Medium-size jet pump and additional pump.
For whirlpools and added support in water circuits.

Details

Connection: 230V, 400V
Flow rate Q in m³/h: 15
Motor performance in kW (P2): 0,75
Pool size in m³: 30 - 60, 30 - 60
Total head H in m WS: 8, 8

Materials used

Diffuser: PP GF 30, PP GF 30
Gland housing: PP GF 30
Impeller: PP GF 30
Intermediate housing: PP GF 30
Mechanical seal: carbon / ceramic / NBR
Pump casing: PP TV 20 / GF 10
Screws: Stahl, verzinkt

Field of application

The BADU 43 pump series with its flow rate from 15 m³/h to 32 m³/h are the perfect jets and filter pumps for whirlpools.

Design

Monoblock-type pump with a closed bellows-type mechanical seal mounted on a plastic shaft protector sleeve. Motor/pump shaft has no contact with the pool water! Complete electrical separation.

Motors

Special motors on request.

Miscellaneous

The above mentioned pumps can be used for pool water with a salt concentration of up to 0.5%, i.e. 5 g/l.
For higher salt concentrations please contact the company SPECK Pumpen.

Downloads

- Spare parts list
- Catalogue page
- Characteristics
- EC declaration of conformity
- Dimensional drawing