

BADU[®] 44/8



Convenient monoblock-type pump with self-draining unit.
For larger bath tubs and whirlpools.

Details

Flow rate Q in m³/h: 3
Motor performance in kW (P2): 0,25
Pool size in m³: 1 - 30
Total head H in m WS: 8, 8

Materials used

Gland housing: PP TV 40, PP TV 40
Impeller: PA 66 GF 30 / PC
Mechanical seal: carbon / ceramic / NBR
Pump casing: PP, PP
Screws: Stahl, verzinkt

Field of application

The BADU 44 pump series with self-draining unit and a flow rate of up to 14 m³/h are the perfect jet pumps for bath tubs.

Design

Monoblock-type pump with integrated self-draining unit. The bellow-type mechanical seal is mounted on a plastic shaft protector sleeve. Motor/pump shaft has no contact with the pool water providing complete electrical separation.

Motors

Special motors on request.

Miscellaneous

The above mentioned pumps can be used for pool water with a salt concentration of up to 0.5%, i.e. 5 g/l.

For higher salt concentrations please contact the company SPECK Pumpen.

Downloads

- [Spare parts list](#)
- [Catalogue page](#)
- [Characteristics](#)
- [EC declaration of conformity](#)
- [Dimensional drawing](#)