# **BADU<sup>®</sup> 46/10**



Solid, medium-size jet pump with self-draining unit. For bath tubs, whirlpools and spa facilities.

#### **Details**

Flow rate Q in m<sup>3</sup>/h: 10

Motor performance in kW (P2): 0,45 Pool equipment: Circulation pumps

Pool size in m<sup>3</sup>: 1 - 30 Pool type: Whirlpool

Total head H in m WS: 8, 8

## **Materials used**

Gland housing: PP TV 40, PP TV 40 Mechanical seal: carbon / ceramic / NBR

Pump casing: PP TV 40 Screws: Messing / Edelstahl

## Field of application

The BADU 46 pumps empty remaining water automatically. Flow rate is from 5 m<sup>3</sup>/h to 20 m<sup>3</sup>/h at 8 m, the ideal pumps for jacuzzis and whirlpools.

## Design

Monoblock-type pump. The bellow-type mechanical seal is mounted on a plastic shaft protector sleeve. Motor/pump shaft has no contact with the pool water providing complete electrical

separation.

## **Motors**

Special motors on request.

## **Miscellaneous**

The above mentioned pumps can be used for pool water with a salt concentration of up to 0.5%, i.e. 5 g/l.

For higher salt concentrations please contact the company SPECK Pumpen.

## **Downloads**

- Spare parts list
- Catalogue page
- Characteristics
- EC declaration of conformity
- Dimensional drawing