

BADU[®] 47/10



Connection option for BADU 46 medium-size jet pump.
For bath tubs, whirlpools and spa facilities.

Details

Flow rate Q in m³/h: 10
Motor performance in kW (P2): 0,45
Pool equipment: Circulation pumps
Pool size in m³: 1 - 30
Pool type: Whirlpool
Total head H in m WS: 14

Materials used

Gland housing: PP TV 40, PP TV 40
Mechanical seal: carbon / ceramic / NBR
Pump casing: PP TV 40
Screws: Messing / Edelstahl

Field of application

The BADU 47 series with its flow rate of 6 to 23 m³/h at 8 m is the ideal pump for whirlpools and spa applications.

Design

Monoblock-type pump. The bellows-type mechanical seal is mounted on a plastic shaft protector sleeve. Motor/pump shaft has no contact with the pool water providing complete electrical

separation.

Motors

Special motors on request.

Miscellaneous

The above mentioned pumps can be used for pool water with a salt concentration of up to 0.5%, i.e. 5 g/l.

For higher salt concentrations please contact the company SPECK Pumpen.

Downloads

- [Spare parts list](#)
- [Catalogue page](#)
- [Characteristics](#)
- [EC declaration of conformity](#)
- [Dimensional drawing](#)