

BADU[®] Delta-MK 16



Performance features:

- Without mechanical seal
- Maintenance-free motor with high-performance ball bearings
- Especially quiet and efficient
- Newly configured hydraulics
- Transparent lid with LED lighting
- PVC connection pieces
- Interior drain plugs, thus no danger of breakage

Details

Class: PREMIUM

Connection: 230V, 400V

Flow rate Q in m³/h: 16

Installation: Built-in pool

Motor performance in kW (P2): 0,65

Pool equipment: Circulation pumps

Pool type: Innenpool

Strainer basket in mm: ca. 2,2 x 2,2

Strainer capacity in l: ca. 4

Total head H in m WS: 8

Materials used

Impeller: PPE GF 30

Intermediate housing: PP GF 30

Lid: PC, transparent / PA 66 GF 30

Mechanical seal: carbon / ceramic / NBR

Pump casing: PP GF 30

Screws: Edelstahl

Strainer basket: PP

Field of application

Swimming pool water circulation through a filter system. The pump can be installed max. 1.5 m above or 3 m below water level.

Design

Monoblock-type pump with integrated strainer tank. Motor/pump shaft has no contact with the pool water, providing complete electrical separation.

Motors

Special motors on request.

Miscellaneous

The pumps, as described, can be used for pool water with a salt concentration of up to 0.5%, i.e. 5 g/l. For higher salt concentrations please contact the company SPECK Pumpen.

Downloads

- [3D model](#)
- [Spare parts list](#)
- [Catalogue page](#)
- [Characteristics](#)
- [EC declaration of conformity](#)
- [Dimensional drawing](#)