BADU® Delta-MK 8



Performance features:

- Without mechanical seal
- Maintenance-free motor with high-performance ball bearings
- Especially quiet and efficient
- Newly configured hydraulics
- Transparent lid with LED lighting
- PVC connection pieces
- Interior drain plugs, thus no danger of breakage

Details

Class: PREMIUM
Connection: 230V, 400V
Flow rate Q in m³/h: 9
Installation: Built-in pool
Motor performance in kW (P2): 0,30
Pool equipment: Circulation pumps
Pool type: Innenpool
Strainer basket in mm: ca. 2,2 x 2,2
Strainer capacity in l: ca. 4
Total head H in m WS: 8

Materials used

Impeller: PPE GF 30
Intermediate housing: PP GF 30
Lid: PC, transparent / PA 66 GF 30
Mechanical seal: carbon / ceramic / NBR
Pump casing: PP GF 30
Screws: Edelstahl
Strainer basket: PP

Field of application

Swimming pool water circulation through a filter system. The pump can be installed max. 1.5 m above or 3 m below water level.

Design

Monoblock-type pump with integrated strainer tank. Motor/pump shaft has no contact with the pool water, providing complete electrical separation.

Motors

Special motors on request.

Miscellaneous

The pumps, as described, can be used for pool water with a salt concentration of up to 3%, i.e. 5 g/l. For higher salt concentrations please contact the company SPECK Pumpen.

Downloads

- 3D model
- Spare parts list
- Catalogue page
- Characteristics
- EC declaration of conformity
- Dimensional drawing