

# BADU<sup>®</sup> Delta-MK Eco VS



Performance features:

- Without mechanical seal
- Motor display with intuitive control
- Low energy consumption
- Especially quiet and efficient
- Newly configured hydraulics
- Transparent lid with LED lighting
- PVC connection pieces
- Interior drain plugs, thus no danger of breakage
- Efficient energy saving due to permanent magnet motor
- External control via potential-free contacts e.g. with the BADU Eco Logic

**Products in the BADU Delta series are only available via specialist retailers. Their high quality and technical demands require specialist knowledge for the planning and installation.**

## Details

Class: PREMIUM

Installation: Built-in pool

Motor performance in kW (P2): 1,10

Pool equipment: Circulation pumps

Pool type: Innenpool

Strainer basket in mm: ca. 2,2 x 2,2

Strainer capacity in l: ca. 4

Total head H in m WS: 8

## Materials used

Impeller: PPE GF 30

Intermediate housing: PP GF 30

Lid: PC, transparent / PA 66 GF 30

Mechanical seal: carbon / ceramic / NBR  
Pump casing: PP GF 30  
Screws: Edelstahl  
Strainer basket: PP

## Field of application

Swimming pool water circulation through a filter system. The pump can be installed max. 3 m above or below water level.

## Design

Monoblock-type pump with integrated strainer tank. Motor/pump shaft has no contact with the pool water, providing complete electrical separation.

## Motors

Special motors on request.

## Miscellaneous

Also available in special design. The pumps, as described, can be used for pool water with a salt concentration of up to 0.5%, i.e. 5 g/l. For higher salt concentrations please contact the company SPECK Pumpen.

## Downloads

- [General operation manual](#)
- [3D model](#)
- [Spare parts list](#)
- [Catalogue page](#)
- [EC declaration of conformity](#)
- [Dimensional drawing](#)