

BADU[®] EasyFit 12



With the BADU EasyFit the often time-consuming task of installing a new circulation pump into an existing filter unit is a thing of the past. The BADU EasyFit fits almost every unit, regardless of the manufacturer: 6 adaptable connection sets provide inlet and outlet connections which are compatible with varying pipe dimensions and connection options. Variable pump feet ensure that the pump can take over the exact position of the old pump.

[Here](#) you will find our product video.

Details

Class: PREMIUM

Filter size in mm: 500 - 610, 500 - 610

Flow rate Q in m³/h: 12, 12

Installation: Built-in pool

Motor performance in kW (P2): 0,45

Pool equipment: Circulation pumps

Pool size in m³: 30 - 60, 30 - 60

Pool type: Innenpool

Strainer capacity in l: ca. 3, ca. 3

Total head H in m WS: 8, 8

Materials used

Diffuser: PP TV 40 / PP GF 30

Gland housing: PP TV 40, PP TV 40

Impeller: PA 66 GF 30 + PC / PP GF 30

Intermediate housing: PP GF 30

Lid: PC, transparent / PP GF 30

Mechanical seal: carbon / ceramic / NBR

Pump casing: PP GF 30

Screws: Edelstahl

Strainer basket: PP

Field of application

Swimming pool water circulation through a filter system. The pump can be installed max. 3 m above or below water level.

Design

Monoblock-type pump with integrated strainer tank. The bellow-type mechanical seal is mounted on a plastic shaft protector sleeve. Motor/pump shaft has no contact with the pool water providing complete electrical separation.

Miscellaneous

The pumps, as described, can be used for pool water with a salt concentration of up to 0.5%, i.e. 5 g/l.

For higher salt concentrations please contact the company SPECK Pumpen.

Downloads

- [Spare parts list](#)
- [Catalogue page](#)
- [Characteristics](#)
- [EC declaration of conformity](#)
- [Dimensional drawing](#)