

BADU[®] EasyFit Eco VS



This universal pump combines the high installation flexibility of the BADU EasyFit with the wide field of application and the energy efficiency of the BADU 90 Eco VS. Adaptable connection sets and variable pump feet allow the pump to take over the exact position of the old pump in an existing unit.

The pump is delivered ready for connection with a 5-wire control cable, cable and plug.
[Here you will find our product video.](#)

Details

Class: PREMIUM

Filter size in mm: 400 - 500

Flow rate Q in m³/h: 28

Installation: Built-in pool

Motor performance in kW (P2): 1,10

Pool equipment: Circulation pumps

Pool size in m³: 30 - 90

Pool type: Innenpool

Strainer basket in mm: ca. 3,2 x 2,6

Strainer capacity in l: ca. 3

Total head H in m WS: 8

Materials used

Diffuser: PA 66 GF 30/PP GF 30

Gland housing: PP TV 40

Glue socket: ABS

Impeller: PP GF 30

Intermediate housing: PP GF 30

Lid: PC, transparent / PP GF 30

Mechanical seal: carbon / ceramic / NBR

Pump casing: PP GF 30
Screws: Edelstahl
Strainer basket: PP

Field of application

Swimming pool water circulation through a filter system. The pump can be installed max. 3 m above or below water level.

Design

Monoblock-type pump with integrated strainer tank. The bellow-type mechanical seal is mounted on a plastic shaft protector sleeve. Motor/pump shaft has no contact with the pool water providing complete electrical separation.

Downloads

- [Spare parts list](#)
- [Catalogue page](#)
- [Characteristics](#)
- [EC declaration of conformity](#)
- [Dimensional drawing](#)