

# BADU<sup>®</sup> Gamma 15



With the BADU Gamma swimming pool pump you have the usual first-class material quality. It is extremely quiet and has improved hydraulics with optimised water flow. Optional inner or outer threads provide great flexibility during installation.

## Details

Class: PREMIUM  
Connection: 230V, 400V  
Flow rate Q in m<sup>3</sup>/h: 15  
Installation: Built-in pool  
Motor performance in kW (P2): 0,55  
Pool equipment: Circulation pumps  
Pool type: Naturpool / Schwimmteich  
Strainer basket in mm: ca. 3,2 x 2,6  
Strainer capacity in l: ca. 3, ca. 3  
Total head H in m WS: 8, 8

## Materials used

Diffuser: PA 66 GF 30/PP GF 30  
Gland housing: PP TV 40, PP TV 40  
Impeller: PP GF 30  
Intermediate housing: PP TV 40, PP TV 40  
Lid: PC, transparent / PA 66 GF 30, PC, transparent / PA 66 GF 30  
Mechanical seal: carbon / ceramic / NBR  
Pump casing: PP GF 30  
Screws: stainless steel 1.4301  
Strainer basket: PP

## Field of application

Swimming pool water circulation through a filter system. The pump can be installed max. 3 m

above or below water level.

## Design

Monoblock-type pump with integrated strainer tank. The bellow-type mechanical seal is mounted on a plastic shaft protector sleeve. Motor/pump shaft has no contact with the pool water providing complete electrical separation.

## Motors

Special motors on request.

## Miscellaneous

The pumps, as described, can be used for pool water with a salt concentration of up to 0.5%, i.e. 5 g/l.

For higher salt concentrations please contact the company SPECK Pumpen.

## Downloads

- [3D model](#)
- [Spare parts list](#)
- [Catalogue page](#)
- [Characteristics](#)
- [EC declaration of conformity](#)
- [Dimensional drawing](#)