BADU® Gamma 23



With the BADU Gamma swimming pool pump you have the usual first-class material quality.It is extremely quiet and has improved hydraulics with optimised water flow. Optional inner or outer threads provide great felxibility during installation.

Details

Class: PREMIUM
Connection: 230V, 400V
Flow rate Q in m³/h: 23
Installation: Built-in pool
Motor performance in kW (P2): 1,00
Pool equipment: Circulation pumps
Pool type: Naturpool / Schwimmteich
Strainer basket in mm: ca. 3,2 x 2,6
Strainer capacity in l: ca. 3, ca. 3
Total head H in m WS: 8, 8

Materials used

Diffuser: PA 66 GF 30/PP GF 30
Gland housing: PP TV 40, PP TV 40
Impeller: PP GF 30
Intermediate housing: PP TV 40, PP TV 40
Lid: PC, transparent / PA 66 GF 30, PC, transparent / PA 66 GF 30
Mechanical seal: carbon / ceramic / NBR
Pump casing: PP GF 30
Screws: stainless steel 1.4301
Strainer basket: PP

Field of application

Swimming pool water circulation through a filter system. The pump can be installed max. 3 m

above or below water level.

Design

Monoblock-type pump with integrated strainer tank. The bellow-type mechanical seal is mounted on a plastic shaft protector sleeve. Motor/pump shaft has no contact with the pool water providing complete electrical separation.

Motors

Special motors on request.

Miscellaneous

The pumps, as described, can be used for pool water with a salt concentration of up to 0.5%, i.e. 5 g/l.
For higher salt concentrations please contact the company SPECK Pumpen.

Downloads

- 3D model
- Spare parts list
- Catalogue page
- Characteristics
- EC declaration of conformity
- Dimensional drawing