

BADU[®] Gamma 32



With the BADU Gamma swimming pool pump you have the usual first-class material quality. It is extremely quiet and has improved hydraulics with optimised water flow. Optional inner or outer threads provide great flexibility during installation.

Details

Class: PREMIUM

Connection: 230V, 400V

Flow rate Q in m³/h: 32

Installation: Built-in pool

Motor performance in kW (P2): 1,50

Pool equipment: Circulation pumps

Pool type: Naturpool / Schwimmteich

Strainer basket in mm: ca. 3,2 x 2,6

Strainer capacity in l: ca. 3, ca. 3

Total head H in m WS: 8, 8

Materials used

Diffuser: PA 66 GF 30/PP GF 30

Gland housing: PP TV 40, PP TV 40

Impeller: PP GF 30

Lid: PC, transparent / PA 66 GF 30, PC, transparent / PA 66 GF 30

Mechanical seal: carbon / ceramic / NBR

Pump casing: PP GF 30

Screws: stainless steel 1.4301

Strainer basket: PP

Field of application

Swimming pool water circulation through a filter system. The pump can be installed max. 3 m above or below water level.

Design

Monoblock-type pump with integrated strainer tank. The bellow-type mechanical seal is mounted on a plastic shaft protector sleeve. Motor/pump shaft has no contact with the pool water providing complete electrical separation.

Motors

Special motors on request.

Miscellaneous

The pumps, as described, can be used for pool water with a salt concentration of up to 0.5%, i.e. 5 g/l.

For higher salt concentrations please contact the company SPECK Pumpen.

Downloads

- [3D model](#)
- [Spare parts list](#)
- [Catalogue page](#)
- [Characteristics](#)
- [EC declaration of conformity](#)
- [Dimensional drawing](#)