

BADU[®] Gamma Eco VS



With the BADU Gamma Eco VS swimming pool pump you have the usual first-class material quality. It is extremely quiet and has improved hydraulics with optimised water flow. Optional inner or outer threads provide great flexibility during installation. The permanent magnet motor provides efficient energy savings. Can be controlled using the BADU Eco Logic remote control.
The pump is delivered ready for connection with a 5-wire control cable, cable and plug.

Details

Class: PREMIUM
Installation: Built-in pool
Motor performance in kW (P2): 1,10
Pool equipment: Circulation pumps
Pool type: Naturpool / Schwimmteich
Strainer basket in mm: ca. 3,2 x 2,6
Strainer capacity in l: ca. 3, ca. 3
Total head H in m WS: 8, 8

Materials used

Diffuser: PA 66 GF 30
Gland housing: PP TV 40, PP TV 40
Impeller: PP GF 30
Intermediate housing: PP TV 40, PP TV 40
Lid: PC, transparent / PA 66 GF 30, PC, transparent / PA 66 GF 30
Mechanical seal: carbon / ceramic / NBR
Pump casing: PP GF 30
Screws: stainless steel 1.4301
Strainer basket: PP

Field of application

Swimming pool water circulation through a filter system. The pump can be installed max. 3 m

above or below water level.

Design

Monoblock-type pump with integrated strainer tank. The bellow-type mechanical seal is mounted on a plastic shaft protector sleeve. Motor/pump shaft has no contact with the pool water providing complete electrical separation.

Motors

Special motors on request.

Miscellaneous

The pumps, as described, can be used for pool water with a salt concentration of up to 0.5%, i.e. 5 g/l.

For higher salt concentrations please contact the company SPECK Pumpen.

Downloads

- [3D model](#)
- [Spare parts list](#)
- [Catalogue page](#)
- [Characteristics](#)
- [EC declaration of conformity](#)
- [Dimensional drawing](#)