

# BADU<sup>®</sup>JET Smart Final assembly kit 400 V



The compact submerged unit is installed in the pool wall. The direction nozzle control and stepless regulation of the water and air flow allow you to adapt the unit to suit your needs - whether underwater massage, bubble bath, wave pool or no-turn swimming. Its clear design, simple installation and minimal maintenance requirements increase the fun factor of the BADUJET Smart.

Here you will find our product video.

## Details

Class: ALLROUND

Extras: Aquafitness, Aquafitness

Motor performance in kW (P2): 2,20

Pool equipment: Counter swim units

Pump flow rate in m<sup>3</sup>/h: 45

Verwendung: Neubau

## Materials used

Ball valves and fittings: PVC, PVC

Innenteile: ABS / Edelstahl, ABS / Edelstahl

Main housing: ABS, ABS

Nozzle housing: ABS, ABS

Suction/pressure line: PVC

## Field of application

For mounting into walls of all pool models, as a conversation piece, for fitness training, as a wave or air bubble bath, for underwater massages (consult physician), for endless no-turn swimming, even in the smallest pool.

## Design

A powerful jet pump is connected via suction and pressure lines with the plastic jet housing which is flush-mounted in the pool wall. The water is drawn into the jet pump at a low velocity through a large number of openings all around the nozzle housing and it is pumped back to the pool in a powerful jet which can be regulated in strength via the nozzle. The pneumatic on/off switch and the regulation for the air intake which gives the sparkling bubble bath effect are both integrated in the nozzle housing.

## Miscellaneous

Permitted limits for stainless steel parts:

Chloride ion content max. 400 mg/l, pH value 6.8 to 8.2.

Please contact SPECK Pumpen before installing a submerged counter swim unit in a saltwater pool.

## Downloads

- [General operation manual](#)
- [Spare parts list](#)
- [Catalogue page](#)
- [EC declaration of conformity](#)
- [Dimensional drawing](#)