

# Fire extinguishing system Feuercell II FC 40-40



- Compact
- Low noise operation
- Fully-automatic
- Ready for connection
- Easy to install

## Details

Flow rate Q in m<sup>3</sup>/h: 36

Motor performance in kW (P2): 15,00

Total head H in m WS: 87

## Field of application

- > Fire water supply
- > Mains disconnection
- > Irrigation
- > Water supply

## Design

- > Compact
- > Low noise operation
- > Fully-automatic

- > Ready for connection
- > Easy to install

## Miscellaneous

- > Feed tank (delivery for fire fighting water) according to DIN 14462 and DIN 1988, part 600
- > Overflow according to DIN EN 13077
- > Supply line rinse according to DIN 1988, part 600
- > Booster unit according to DIN EN 806-2

Your benefits, at a glance:

- > Germany-wide service
- > Ideal for sanitising existing properties
- > Emergency hotline – via GSM module (optional)
- > Feed tank with German association for gas and water sign of approval (Reg.-Nr. AS-0625CN0018)
- > Motor ball valve with battery (therefore no pressure blows in the supply line)
- > Integrated emergency line
- > Temperature monitoring and weekly test runs

## Downloads

- [General operation manual](#)
- [DEKRA certificate](#)
- [DVGW certificate](#)
- [Catalogue page](#)
- [Characteristics](#)
- [EC declaration of conformity](#)
- [Dimensional drawing](#)