

# BADU<sup>®</sup> Top II/14



A classic in the BADU series, this pump is especially designed for medium-size, above ground pools, partially embedded pools and smaller swimming ponds. Thanks to the large pumping capacity, an automatic pool cleaner can also be attached.

## Details

Class: ALLROUND

Filter size in mm: 610 - 650, 610 - 650

Flow rate Q in m<sup>3</sup>/h: 14, 14

Installation: Built-in pool

Motor performance in kW (P2): 0,65

Pool equipment: Circulation pumps

Pool size in m<sup>3</sup>: 30 - 90, 30 - 90

Pool type: Innenpool

Strainer basket in mm: ca. 3,2 x 2,6

Strainer capacity in l: ca. 3, ca. 3

Total head H in m WS: 8, 8

## Materials used

Diffuser: PP TV 40, PP TV 40

Gland housing: PP TV 40, PP TV 40

Impeller: PA 66 GF 30 / PC

Intermediate housing: PP TV 40, PP TV 40

Mechanical seal: carbon / ceramic / NBR

Pump casing: PP TV 20, PP TV 20

Screws: Stahl, verzinkt

Strainer basket: PP

## Field of application

Swimming pool water circulation through a filter system. The pump can be installed max. 2 m

above or max. 3 m below water level.

## Motors

Special motors on request.

## Miscellaneous

The pumps, as described, can be used for pool water with a salt concentration of up to 0.5%, i.e. 5 g/l. For higher salt concentrations please contact the company SPECK Pumpen.

## Downloads

- [3D model](#)
- [Spare parts list](#)
- [Catalogue page](#)
- [Characteristics](#)
- [EC declaration of conformity](#)
- [Dimensional drawing](#)