Fire extinguishing system Feuercell II FC 40-20



- Compact
- Low noise operation
- Fully-automatic
- Ready for connection
- Easy to install

Details

Flow rate Q in m³/h: 36
Motor performance in kW (P2): 7,50
Total head H in m WS: 43

Field of application

> Fire water supply
> Mains disconnection
> Irrigation
> Water supply

Design

> Compact
> Low noise operation
> Fully-automatic

> Ready for connection
> Easy to install

Miscellaneous

> Feed tank (delivery for fire fighting water) according to DIN 14462 and DIN 1988, part 600
> Overflow according to DIN EN 13077
> Supply line rinse according to DIN 1988, part 600
> Booster unit according to DIN EN 806-2
Your benefits, at a glance:
> Germany-wide service
> Ideal for sanitising existing properties
> Emergency hotline – via GSM module (optional)
> Feed tank with German association for gas and water sign of approval
(Reg.-Nr. AS-0625CN0018)
> Motor ball valve with battery (therefore no pressure blows in the supply line)
> Integrated emergency line
> Temperature monitoring and weekly test runs

Downloads

- General operation manual
- DEKRA certificate
- DVGW certificate
- Catalogue page
- Characteristics
- EC declaration of conformity
- Dimensional drawing